



MULTIS EP 2

DESCRIPTION

Multi-purpose Extreme Pressure Lithium/Calcium grease, NLGI grade 2.

APPLICATIONS

MULTIS EP 2 is a true multi-purpose grease, formulated for lubrication of loaded slide-ball, and roller-bearings, wheelbearings, universal joints, chassis, and various shock loaded or vibrating applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions.

Suitable as general-purpose grease for industrial applications requiring a NLGI 2 grade.

Extreme Pressure grease.

SPECIFICATIONS

ISO 6743-9: L-XCCEB 2

DIN 51 502: KP2K -30

ADVANTAGES

- Because of its true multi-purpose character **MULTIS EP 2** may replace a wide range of greases, allowing stock rationalization and simplification of maintenance.
- Forms a durable lubrication film, resulting in reduction of maintenance and down-time costs.
- Miscible with most other conventional soap greases.
- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent adhesion to metal.
- Good thermal stability, leading to high resistance to temperature variations.
- **MULTIS EP 2** does not contain lead, or other heavy metals considered harmful to human health and the environment.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.

TotalEnergies Lubricants

SA 552 006 454 RCS Nanterre - France

RECOMMENDATIONS

Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

For upgrading towards a multipurpose grease with improved high temperature resistance :

MULTIS COMPLEX EP 2

For upgrading towards a biosourced and biodegradable version with improved cold properties :

BIOMULTIS EP 2

TYPICAL CHARACTERISTICS

| PROPERTIES | METHODS | UNITS | MULTIS EP 2 |
|--|---|--------------------------|-------------------|
| Soap/thickener | | - | Lithium / Calcium |
| NLGI Grade | ASTM D 217/DIN 51 818 | - | 2 |
| Color | Visual | - | Brown |
| Appearance | Visual | - | Smooth |
| Operating temperature range | | °C | -30 à 120 |
| Penetration at 25°C | ASTM D 217/DIN 51 818 | 0.1 mm | 265-295 |
| 4-balls weld load | DIN 51 350-4 | daN | 260 - 280 |
| 4-balls weld load | ASTM D 2596 | Kgf | 315 |
| 4-balls wear scar | ASTM D 2266 | mm | 0,6 |
| Anti-rust performance SKF-EMCOR | DIN 51 802/IP220/NFT 60-135/ ISO 11007 | Rating | 0 - 0 |
| Dropping point | IP 396/DIN ISO 2176 | °C | >190 |
| Kinematic viscosity of the base oil at 40°C | ASTM D 445/DIN 51 562-1/ISO 3104/IP71 | mm ² /s (cSt) | 150 |

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.

TotalEnergies Lubricants

SA 552 006 454 RCS Nanterre - France