



Nevastane Silicone Spray

DESCRIPTION

Multipurpose, NSF-H1-certified Silicone Oil, suitable for incidental food contact

APPLICATIONS

- NEVASTANE SILICONE SPRAY contains a high viscosity silicone oil with excellent stability to provide maximum lubrication.
- NEVASTANE SILICONE SPRAY is multipurpose, with a wide operating temperature range (-60°C to +230°C): small machines and chains subject to extreme temperatures, shrink oven chains, conveyors, rails, joints, hinges, locks...
- NEVASTANE SILICONE SPRAY is recommended for the lubrication of numerous applications in food processing industries.
- NEVASTANE SILICONE SPRAY can also be used as a demolding agent.

CAUTION

Due to the container and the presence of solvents:

- Keep away from heat, sparks, and flames.
- Do not expose to heat and temperatures exceeding 50°C.
- Even when empty, do not puncture or incinerate the container

Keep away from daylight, dust, and humidity.

ADVANTAGES

- NEVASTANE SILICONE SPRAY is recommended for use where incidental contact with food may occur. Using maintenance lubricants which have been registered H1 with NSF minimizes your critical control points as required by HACCP.
- Anti-adhesive, anti-static, dielectric, water repellent.
- Anti-rust, anti-corrosion & very good insulation properties; Without effect on metals and plastics.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at www.quick-fds.com.

Shelf life: 2 years from date of manufacture.

- Does not dry, resists to shear and wet atmospheres.
- Non-flammable propellant gas : CO₂
- Can be used upside-down for an easier manipulation of the spray.

TYPICAL CHARACTERISTICS

PROPERTIES	Nevastane Silicone Spray	UNITS	STANDARDS
Aspect	Slippery, transparent film	-	Visual
Color	Colorless	-	Visual
Operating temperature range	-60 to 230°C	°C	-

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at www.quick-fds.com.