

# OSYRIS DWY 6000



*Metalworking*



**TOTAL**

## APPLICATIONS

- Solvent-based fluid for corrosion protection specifically developed to present:
  - superior water displacement capability
  - long-term protection
  - short drying time
  - low odor.

## SPECIFICATIONS

- **OSYRIS DWY 6000** complies with Standard ISO 6743/8 (1987) : REE category.

## ADVANTAGES

- **OSYRIS DWY 6000** is specifically designed for corrosion protection in the metal processing industry.
- **OSYRIS DWL 6000** is specifically developed to have a low odor.
- **OSYRIS DWY 6000** presents a superior water displacement capability.
- **OSYRIS DWY 6000** coats the metal surface with a thin, soft and non drying protective film.
- **OSYRIS DWY 6000** provides protection for about eight months during indoor storage and for about three months during outdoor and sheltered storage.
- **OSYRIS DWY 6000** presents a short drying time.
- **OSYRIS DWY 6000** can be easily applied:
  - with a brush
  - by spraying
  - by immersion.
- **OSYRIS DWY 6000** can be easily removed with:
  - diluted alkaline detergents
  - solvents (liquid or vapour phase)
  - mechanical treatments.

TYPICAL CHARACTERISTICS	METHODS	UNITS	OSYRIS DWY 6000
Aspect	-	-	Clear
Density (@ 15°C)	EN ISO 12185	kg/m <sup>3</sup>	800
Flash Point	EN ISO 2719	°C	63
Viscosity (@ 40°C)	DIN 51562	mm <sup>2</sup> /s	2.8
Thickness of film	-	µm	2.4

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS  
INDUSTRIE**

31-07-2015 (supersedes 19-06-2012)

OSYRIS DWY 6000

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).