



Diel MS 7000

DESCRIPTION

Electro Discharge Machine Fluid.

APPLICATIONS

- **Diel MS 7000** is a multifunctional fluid particularly suitable for semi finishing and finishing operations when the shapes are complex and with very accurate dimensions.
- **Diel MS 7000** is suitable for EDM, Machines AGIE-CHARMILLES, ONA, ZIMMLER & KLEIN, NASSOVIA, WALDRICH SIEGEN.

SPECIFICATION

- NADCAP (DMP66).

RECOMMENDATIONS

- **Diel MS 7000** is partly biodegradable according to OECD test,
- Good resistance to oxidation,
- High flash point,
- Very narrow petroleum cut for low volatility,
- Very low aromatics content.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com

TYPICAL CHARACTERISTICS

Typical characteristics	Methods	Units	Diel MS 7000
Appearance	Visual	-	Transparent
Colour	ASTM D 156	-	0.5
Density	ISO 3675	kg/m ³	812
Viscosity at 20 °C	ISO 3104	mm ² /s	3.4
Flash point Pensky-Martens	ISO 2719	°C	102
Pour Point	ISO 3016	°C	- 50
Total aromatics content	TOTAL I L 14 (DMSO - UV)	Weight %	0.01

The characteristics shown in this table are typical values given for illustrative purposes.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com