



Glacelf Supra

MEG-based OAT antifreeze

DESCRIPTION

Glacelf Supra is a “very long-life” antifreeze formulated with monoethylene glycol (MEG) and Organic Additive Technology (OAT) to deliver exceptional protection against corrosion, freezing, and boiling.

This environmentally friendly formula is completely free of 2-EHA, phosphates, amines, nitrites, boron, nitrates, and silicates.

APPLICATIONS

Engine Cooling: Stationary Diesel and Gas engines needing a freeze protection from -17°C to -50°C depending on dilution (see table below).

Industrial Heat Transfer: Ideal for use in diverse industrial systems, including cogeneration, wind turbine, machine tools, ... (*non-exhaustive list*)

Glacelf Supra (volume%)	30	40	50	60
Freezing Point, ASTM D1177 (°C)	-17	-26	-37	-50

ADVANTAGES

Very long-term corrosion protection: Organic additives ensure a long-term action to offer maximum protection against any type of corrosion, erosion and cavitation, even at high temperatures.

Maximum Heat Transfer: Ensured by the formation of a strategic, localized passivation layer, which minimizes thermal resistance and maximizes efficient heat dissipation.

Deposit formation: Exceptional thermal stability prevents mineral deposits, especially in critical areas like liners, cylinder heads, and heat exchangers.

Cost reduction: long-life formulation allows for extended drain intervals, reducing coolant recycling costs.

Muti-material compatibility: Compatible with a wide range of elastomers (EPDM, HNBR, etc.), plastics (PP, PA, PTFE, etc.), and metals (iron, steel, aluminum, etc.)

Environment: Formulated with carefully selected additives to minimize environmental impact and ensure maximum consumer safety



This coolant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at ms-sds.totalenergies.com

TotalEnergies Lubrifiants
SA 552 006 454 RCS Nanterre - France

INTERNATIONAL SPEC.

Glacelf Supra complies with the following standards:

- ASTM D3306*
- AFNOR NFR 15-601
- BS 6580*
- GB 29743.1*

*except foaming characteristics

OEM SPECIFICATIONS

Official OEM approval: **CAT-MWM** (0199-99-2091), **Jenbacher** (TA 1000-0200), **MTU** (MTL 5048), **Tedom**, **SNCF**

Suitable for use: **MAN** (324 type SNF), **Cummins** (CES 14439/14603), **Deutz** (DQC CB-14), **Bergen** (2.13.01), **Waukesha**, **Wärtsilä**, **Semt Pielstick**, ... (non-exhaustive list)

TYPICAL CHARACTERISTICS

PROPERTIES	VALUES	UNITS	STANDARDS
Color	Fluorescent Yellow		Visual
Density (20°C)	1,115	Kg/l	ASTM D5931
pH	8,5		ASTM D1287
Reserve Alkalinity, to inflection point	37.5	ml HCl 0,1N	ASTM D1121
Boiling Point	179	°C	ASTM D1120

Further technical data are available upon request.

RECOMMENDATIONS

Dilution: Antifreeze/Concentrate. Dilute with demineralized water before final use. Do not use tap water or other untreated water sources.

Compatibility: When diluted, Glacelf Supra should be compatible with most other MEG-based OAT coolant. Exclusive use of Glacelf Supra is however recommended for optimum performance.

Monitoring: Extend coolant life and optimize maintenance with LubAnac Coolant analysis.

Shelf life: Glacelf Supra can be stored for 8 years in unopened recipients without any effect on the product quality or performance. It is strongly recommended to use new non-translucent containers, and where possible packages with a UV filter.

Storage: Glacelf Supra should be stored above -20°C and below 30°C. Periods of exposure to temperatures above 35°C should be minimized.

Toxicity/Safety: For toxicity information, safe handling and disposal of the product, please refer to the Safety Data Sheet. This product should not be used to protect the inside of drinking water systems.



This coolant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at ms-sds.totalenergies.com

TotalEnergies Lubrifiants
SA 552 006 454 RCS Nanterre - France